

CONVEYOR



Features

- Durable design, proven over years of manufacture
- High throughput with spring assisted tensioning devices fitted as standard
- Bolted/riveted construction
- Galvanized or stainless steel for sanitary

*With gear-motor
or chain-driven*

Options available for particular applications

*Bigger capacity, double-deck arrangement,
top or side inlet, multi-inlet, multi-outlet
and auto-tensioning available upon request*

SPECIFICATIONS					Power Requirement
Model	MCC-200	MCC-300	MCC-350	MCC-400	Depending on the material bulk density, moisture content, conveying length and inclination
Output Speed	35 / rpm	35 / rpm	48 / rpm	48 / rpm	
Chain Speed	0.32 / sec	0.32 / sec	0.42 / sec	0.42 / sec	
Conveying Capacity	30m ³ /h	45m ³ /h	80m ³ /h	90m ³ /h	
Height (mm)	303	338	338	338	
Width (mm)	256	350	410	460	

*All specifications shown on this catalog are subject to change without prior notice

AGRO-INDUSTRIAL SUPPLIES [M] SDN. BHD.

(Company No.73881-V)

Lot: 25-28 & 32 Kawasan Perusahaan
Bandar Darulaman
06000 Jitra, Kedah Darul Aman
Malaysia

Tel: 604-917 9591
Fax: 604-917 9596
e-mail: info@agro-indus.com
website: www.agro-indus.com

